



- **STAINLESS STEEL BELT CONVEYOR**
- **LOWER POWER REQUIREMENTS**
- **UNI-BODY DESIGN**

**ALL STAINLESS
STEEL FRAME**



**10 TO 15% LIGHTER
THAN THE COMPETITION**

UP TO 350 TPH



NORWOOD
Sales Inc.

**STAINLESS STEEL
COMMERCIAL TENDERS**



Side Discharge Tender Models

ST600 (Mounted Tender)

·2 Compartments

·600 cu/ft.

·Unit Weight: 5,800 lbs.



·Swing Conveyor: 10" x 30'

·Belt: Chevron, 15" x 44'



·Under Hopper Conveyor:
15" x 38'

·Belt: Smooth, 15" x 35.5'



ST933 (Uni-Body D.O.T. Trailer)

·4 Compartments ·933 cu/ft. ·Unit Weight: 15,600 lbs.



·Swing Conveyor: 12" x 30'

·Belt: Chevron, 18" x 59'6"


·Under Hopper Conveyor:
15" x 38'

·Belt: Smooth, 15" x 76'



ST1166 (Uni-Body D.O.T. Trailer)

·5 Compartments ·1166 cu/ft. ·Unit Weight: 18,800 lbs.



·Swing Conveyor: 12" x 30'

·Belt: Chevron, 18" x 59'6"



·Under Hopper Conveyor:
15" x 46'

·Belt: Smooth, 15" x 92'4"



Rear Discharge Tender Model ST900 (Uni-Body D.O.T. Trailer)

·2 Compartments ·900 cu/ft. ·Unit Weight: 13,700 lbs.




- Lift Conveyor: 12" x 24'
- Belt: Chevron, 22" x 59'6"
- Under Hopper Conveyor: 18" x 13'
- Belt: Chevron, 18" x 76'




POWER OPTIONS

Truck Supplied Power



Requires 17 gal./min and 2700 psi. from the wet kit.

Self-Contained Power



Self-contained hydraulic power pack, includes a 38HP Kohler EFI engine, pump and reservoir. Integrated trailer houses two 25-gallon stainless steel tanks for hydraulic fluid and gasoline.

Electric Hydraulic Controls



Controls gates and conveyor. Includes electronic override control box. Cased in a weather-proof stainless steel box.

Wireless Controller



Wirelessly control the engine, gates, and conveyor while having the freedom to move around the tender (Optional).

STANDARD FEATURES

Enclosed Belt Return



The belt return is enclosed to ensure safety and longevity.

Agri-Cover Roll Tarp



Manual and electric tarping systems offered. The roll tarp systems are built in Jamestown, ND by Agri-Cover, Inc.

Aluminum Wheels



Aluminum wheels are corrosion resistant and lightweight.

Versatile Construction



12 gauge 304 stainless steel tank, hopper, conveyor and discharge conveyor.

STANDARD FEATURES CONTINUED

Poke Holes



Allows user the ability to break up settled commodity for continuous conveyor flow.

Access Ladder



Allows user a safe way to climb to view the top of the tender.

Air Ride Suspension



Only standard for ST900, ST933 and ST1166. Air ride system quickly adapts to the load of the trailer and road conditions.

Hydraulic Slide Gate



Hydraulic gates added to easily open and close hopper gates.


OPTIONAL FEATURES

Electric Tank Vibrator



Helps the commodity from settling in the compartments, ensuring a continuous flow to the conveyors.

Split Hoppers



Splits are welded into the hoppers to add even more products to the tender. Gates are often extended when hoppers are split.





Dealer:



NORWOOD
Sales Inc.

11202 38th St. South
Horace, ND 58047

Local: 1 (701) 588-4000
Toll Free: 1 (800) 446-0316
www.norwoodsales.com

